

44000 Series Thermistor Components

100 to 1 Meg Ohm Resistance @ 25°C
 Thermally Conductive Epoxy Coating
 Interchangeability
 Pressed Key Characteristic
 High sensitivity
 RoHS Compliant



44000 SERIES THERMISTORS

Epoxy Encapsulated Precision
 Interchangeable NTC Thermistors utilizing
 high stability pressed-disk ceramic sensor
 for general applications.

FEATURES

- 100 Ohm Resistance @ 25°C
- Interchangeable $\pm 0.1^\circ\text{C}$ or $\pm 0.2^\circ\text{C}$, 0°C to 70°C
- Good Long Term Stability
- High Sensitivity
- Thermally Conductive Epoxy Coating
- RoHS Compliance
- 32 AWG, 3" (7.6 cm) Silver Plated 0.095" (2.4 mm)

APPLICATIONS

- Tight Tolerance Instrumentation
- General Applications Requiring Stability
- Applications Requiring Sensing Small Changes in Temperature
- Non-condensing Moisture Environments
- Allows use in Applications World-wide

stability

MEAS thermistors are chemically stable and are not significantly affected by aging or exposure to strong nuclear radiation. The table below shows typical stability for a representative thermistor, the MEAS 44005.

Typical Thermometric Drift

Operating Temperature	10 months	100 months
0°C	< 0.01°C	< 0.01°C
25°C	< 0.01°C	< 0.02°C
100°C	0.20°C	0.32°C
150°C	1.5°C	Not recommended

44000 Series Thermistor Components

product definition

	Part Number	Zero Power Resistance ohm at 25°C	Beta 0- 50°C (K)	Ratio ohm 25/125°C	Maximum working temperature	Best storage and working temperature
±0.2°C Interchange- ability Tolerance 0 – 70°C	44001A	100	2854	11.49	100°C	-80 + 50°C
	44002A	300	3118	15.15	100°C	-80 + 50°C
	44003A	1000	3271	17.33	100°C	-80 + 50°C
	44004	2252	3891	29.26	150°C	-80 + 120°C
	44005	3000	3891	29.26	150°C	-80 + 120°C
	44007	5000	3891	29.26	150°C	-80 + 120°C
	44006	10K	3574	23.51	150°C	-80 + 120°C
	44008	30K	3810	29.15	150°C	-80 + 120°C
	44011	100K	3988	34.82	150°C	-80 + 120°C
	44014	300K	4276	46.02	150°C	-80 + 120°C
±0.1°C Interchange- ability Tolerance 0 – 70°C	44015	1 meg	4582	61.96	150°C	-80 + 50°C
	44035	1000	3271	17.33	100°C	-80 + 75°C
	44033	2252	3891	29.26	150°C	-80 + 75°C
	44030	3000	3891	29.26	150°C	-80 + 75°C
	44034	5000	3891	29.26	150°C	-80 + 75°C
	44037	6K	3891	29.26	150°C	-80 + 75°C
	44036	10K	3891	29.26	150°C	-80 + 75°C
	44031	10K	3574	23.51	150°C	-80 + 75°C
	44032	30K	3810	29.15	150°C	-80 + 75°C

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

ordering info

NORTH AMERICA

Measurement Specialties, Inc.
910 Turnpike Road
Shrewsbury, MA 01545
Tel: 1-508-842-0516
Fax: 1-508-842-0342

EUROPE

Measurement Specialties, Inc.
Ballybrit Business Park
Galway Ireland
Tel: +353-91-753238
Fax: +353-91-770789

ASIA

北京赛斯维测控技术有限公司
北京市朝阳区望京西路48号
金隅国际C座1002
电话: +86 010 8477 5646
传真: +86 010 5894 9029
邮箱: sales@sensorway.cn
<http://www.sensorway.cn>